

CORRECTED VERSION

Reg'd PCT 12 APR 2005

10/531028

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number  
WO 2004/036603 A1

(51) International Patent Classification<sup>7</sup>: H01F 5/04, 41/10

(21) International Application Number:  
PCT/IB2003/003950

(22) International Filing Date:  
12 September 2003 (12.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
02079281.8 16 October 2002 (16.10.2002) EP

(71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];  
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): HOPMANS, Jan, H., M. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). VAN LIMPT, Cornelis, H., P. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

ROCHE, Adviomus, A. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHEPENS, Nicolaas, J. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).


(74) Agent: DEGUELLE, Wilhelmus, H., G.; Philips Intellectual Property & Standards, Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: LITZ WIRE FIXATION FOR LOW BUILDING HEIGHT



(57) Abstract: The invention relates to a coil (1) comprising at least one pin with an end for anchoring a woven wire, preferably a litz wire resulting in a low building height. Said pin end has a U-shaped part (3) forming a slot (5), said slot (5) has an inner width equal to or smaller than the diameter of the wire (4). It is thereby obtained that the anchoring pin provides a secure anchoring position for the wire during wrapping and that the anchoring pin can be used for litz wire, thereby overcoming the drawbacks in the prior art as well as obtaining a good foundation for the subsequent soldering process. Furthermore it is obtained that height of the coil is smaller than the prior-art coils.

WO 2004/036603 A1